

DAS FOG CANNONS DEMOLITOR 50

Technical Data	Pole	Trailer
Jet length	30/40 m	
Dimensions (Length x Height x Width mm)	800 x 1850 x 1050	1470 x 2160 x 1710
Weight kg	283 kg	321 kg
Site Mobility	Forklift tyne pockets	All Terrain Wheels Towing Hook*
Rotation angle	Up to 340° programmable	
Tilt angle	Manual from -20° to +45°	
Noise levels	< 85 dB(A)	
Minimum pressure	1 Bar	
Rings of nozzles	1	
Nozzles per ring	33	
Washable stainless-steel filter	Yes	
Jet diameter	15 m	
IP degree of protection	IP 55	
Power supply		
Power Supply	32A Plug	
Total electric power installed	9 Kw	
Fan power	5.5 Kw	
Water pump power	2.2 Kw	
Amperage	16 Amp	
Features		
Remote control	Standard	
Rotation system	Standard	
Solenoid valve at water filter inlet	Manual	
High-efficiency electric pump	Standard	
Tilt with servo actuator	Standard	
Water Consumption		
Nozzle Types	0.95 LPM	
Water discharge pressure	12 Bar	
Water consumption	35 L/min	



Key Features

- Suitable for working in extreme conditions.
- High efficiency stainless steel multistage water pump.
- Mounted on a steel base with tyne pockets or trailer for easy positioning.
- High efficiency submersible pump.
- Adjustable rotation angle and tilt.
- Remote activation by remote control

