

DAS FOG CANNONS DEMOLITOR 70

Technical Data	Trailer
Jet length	50/60 m
Dimensions (Length x Height x Width mm)	1880 x 2030 x 1600
Weight kg	670 kg
Site Mobility	All Terrain Wheels Towing Hook *
Rotation angle	Up to 340° programmable
Tilt angle	Electric from -20° to +45°
Noise levels	< 85 dB(A)
Minimum pressure	1 Bar
Rings of nozzles	1
Nozzles per ring	50
Washable stainless-steel filter	Yes
Jet diameter	30 m
IP degree of protection	IP 55
Power supply	
Power Supply	32A Plug
Total electric power installed	16 Kw
Fan power	11 Kw
Water pump power	4 Kw
Amperage	29 Amp
Features	
Remote control	Standard
Rotation system	Standard
Solenoid valve at water filter inlet	Standard
High-efficiency electric pump	Standard
Tilt with servo actuator	Standard
Water Consumption	
Nozzle Types	0.95 LPM
Water discharge pressure	12 Bar
Water consumption	35 L/min



Key Features

- Suitable for working in extreme conditions.
- High efficiency stainless steel multistage water pump.
- Mounted on a steel base with tyne pockets or trailer for easy positioning.
- High efficiency submersible pump.
- Adjustable rotation angle and tilt.
- Remote activation by remote control

