

DAS FOG CANNONS WLP 718

Technical Data	Pole	Trailer
Jet length	70/80 m	
Dimensions (Length x Height x Width mm)	1400 x 2340 x 1350	1880 x 2030 x 1600
Weight kg	881 kg	683 kg
Site Mobility	Forklift tyne pockets	All Terrain Wheels Towing Hook
Rotation angle	Up to 340° programmable	
Tilt angle	Electric from -20° to +45°	
Noise levels	< 85 dB(A)	
Minimum pressure	1 Bar	
Rings of nozzles	3	
Nozzles per ring	50	
Washable stainless-steel filter	Yes	
Jet diameter	35 m	
IP degree of protection	IP 55	
Power supply		
Power Supply	63A 5P Plug	
Total electric power installed	28 Kw	
Fan power	18.5 Kw	
Water pump power	7.5 Kw	
Amperage	50 Amp	
Features		
Remote control	Standard	
Rotation system	Standard	
Solenoid valve at water filter inlet	Standard	
External activation (client or supplied)	Option	
Onboard Weather station onboard control	Option	
High-efficiency electric pump	Standard	
Solenoid valve for each nozzle ring	Standard	
Tilt with servo actuator	Standard	
Switchboard with PLC for automation	Standard	
Water Consumption		



Key Features

- Suitable for working in extreme conditions.
- High efficiency stainless steel multistage water pump.
- Mounted on a steel base with tyne pockets or trailer for easy positioning.
- High efficiency submersible pump.
- Variable water flow rate.
- Stainless steel water filter
- Stainless steel nozzles
- Remote activation by remote control

